

WEY BUTTERFLY VALVES TF13

Flange connections and pressure ratings



9.0.50

Overview flange connections

DN [mm]	40	50	65	80	100	125	150	200	250	300	350	400	450	500	600	700	750	800	900	1000	1100	1200		
 <p>Double flanged Typ TF13</p>	EN 1092-1 PN10/16, ASME 16.5 cl. 150							EN 1092-1 PN10 ASME 16.5 cl. 150																
	EN 1092-1 PN 6 JIS B 2210 10K							EN 1092-1 PN 6, PN 16 JIS B 2210 10K BS 10 Table D+E																
	EN 1092-1 PN 20																							
	JIS B 2210 5K										n.l.		JIS B 2210 5K											
	JIS B 2210 16K							n.l.		n.l.		JIS B 2210 16K												
	AS 2129 Table E																				n.l.			
	BS 10 Table D+E																	n.l.		n.l.				
	n.l.							AWWA C207																

Pressure ratings and operating pressures

DN [mm]	40	50	65	80	100	125	150	200	250	300	350	400	450	500	600	700	750	800	900	1000	1100	1200
max. operating pressures	16 bar							16 bar														
	10 bar							10 bar							10 bar							
	6 bar							6 bar								6 bar						
	3 bar												3 bar									

Standard
 Optional

Further connection standards and pressure ratings on request.